

60WSTRL



Characteristics

Optics

- Polycarbonate Lens
- High transmission 88%
- Non-Removable
- Toughened Glass

Thermal Interface Material

- High thermal conductivity
- Excellent heat transfer

Heat sink

- Aluminum - powder coated
- Excellent thermal conductivity

LED Driver

- Rated Supply: 240V AC, 50/60Hz
- PF > 0.95, THD < 10%,
- Short circuit, open circuit

Mounting

- Pole OD 60 mm max.

Installation

- Easy installation

Weight

- 0.910 Kg

Cable Entry


- 1 Nos.

Housing Color



Powder Coated – Grey (RAL 7024)

Distribution Curve



Features

- Soft and comfortable light to relieve the fatigue of eyes.
- Excellent CRI for actual colour reproduction.
- Energy saving efficiency and low heat produce.
- AL die-cast housing for excellent heat management.
- Quick installation, special design,
- Highly reliable professional design.

Applications

- Roadways, Pathways, Highways
- Industry, Ware-house, Airport,
- Shopping Mall, Parking Lot,
- Sports Hall



60W



105 lm/W



6500K



>70



Polycarbonate Lens



90-305 AC, 50Hz



In-Built, Surge DM 6Kv, CM 10Kv



Non dimmable / 1-10V / DALI



SMD, Bridgelux



Ta: -10°C to 45°C



Lifespan >50000h @ L70 B50



F (for mounting on normally flammable surface)

